



PRO ARMOR

INSTALLATION INSTRUCTIONS

Suzuki LTR450 Frame Skid

S061021

To avoid injury or damage to your ATV, read these instructions before installation.

1. Parts List:

Item	Part Name	Description	Qty
1	Frame Skid Plate		1
2	Hook	.570 Hook	4
3	Bolt, Hex Flange Head	M6x1.0P x 16mm	4
4	Bolt, Hex Flange Head	M6x1.0P x 25mm	1
5	Spacer	1/4 Thick	1
6	Spacer	1/8 Thick	1
7	1" x 2" Adhesive Backed Rubber	Vibration Pad	4

2. Preparation:

- Lock rear brake on bike and plug gas tank vent hose.
- Stand bike upright to rest on the rear grab bar.
- Remove existing frame skid plate.

3. Installation: Follow diagram, working from forward mount down to rear, torque bolts to 12 ft-lbs.

Item #2, #3

Item #2, #3 (2 places)

Item #2, #3

Item #4, #5, #6



Item #7 (apply to inside of skid plate where any vibration occurs)

4. Maintenance: Check fasteners for tightness and re-torque as required.

5. Care and Cleaning: Clean using mild soap.

6. Customer service: For further information call Pro Armor at 951-270-0559